



SPECIFICATION	
MODEL	P1261
TYPE	4-CYCLE WATER COOLED, IN-LINE VERTICAL, UMBO-INTER COOLER
NO. OF CYL-BORE x STROKE	6-123mm x 135mm
COMBUSTION SYSTEM	REINFRANT
COMPRESSOR RATIO	17.1:1
SWEEP VOLUME	11.051 (cc)
ROTATING DIRECTION (FROM FLYWHEEL)	COUNTER CLOCKWISE
DRY WEIGHT	910 (kg)
OUTPUT (1800rpm)	Stand-by 405ps, 298kW Prime 378ps, 278kW
OUTPUT (1500rpm)	Stand-by 370ps, 272kW Prime 328ps, 241kW
INJECTION PUMP TYPE	IN-LINE P TYPE
GOVERNOR TYPE	ELECTRIC
INJECTION NOZZLE	220 (kg/cm ²)
OPENING PRESSURE	1-5-3-6-2-4
FRING ORDER	24V x 45A
ALTERNATOR	24V x 5.4 kW
STARTER	7-Ø755, BLOWER
COOLING FAN	24V x 5.4 kW
THERMOSTAT OPENING TEMP	71°C (FULL 85°C)
OIL CAPACITY (OIL PAN)	23 (lit)
WATER CAPACITY (ENGINE)	19 (lit)

3	21	24	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

ENGINE ASS'Y
 P1261
 65.00506-7530
 Daejeon Infraco Co., Ltd.
 INCHON KOREA